



# Gas Well Supply

5003 Summerbrook Dr, Colleyville, Texas U.S.A 76034

Ph: (530) 846-4400 (530) 846-4499

Fax: (530) 846-4500

## Technical Information

### Chem Flo - 203 Corrosion Inhibitor

#### PRODUCT DESCRIPTION

**Chem Flo - 203** is a performance quat for use in oilfield products not requiring specification starting materials. The ability of **Chem Flo - 203** to film from both oil and water phases makes it ideal for pipeline use. It is recommended for use in water injection systems and high water cut producing wells.

#### PRODUCT FEATURES

- \* Highly Effective / Low Cost Inhibitor
- \* Oil and Water Solubility Characteristics
- \* Corrosion Control In The Presence Of Bacteria

#### PHYSICAL PROPERTIES

<b>Form</b>	Liquid	<b>Solids</b>	≥ 50
<b>Color</b>	Dark Amber	<b>Solubility</b>	
<b>Density @ 60°F (lbs/gal)</b>	7.17 - 7.51	Diesel #2	I
<b>Viscosity @ 75°F</b>	17.5 cps	IPA	D
<b>Flash Point, TCC</b>	69°F	Water	S
<b>Pour Point</b>	-35°F	Xylene	S
<b>pH (neat)</b>	4 - 5		

#### SHIPPING AND HANDLING

**Chem Flo - 203** is shipped in 55 U.S. gallon lined steel drums as a Flammable Liquid/Corrosive, N.O.S. As with any industrial chemical, avoid prolong contact with the skin. In case of skin or eye contact, flush the exposed area with copious amounts of water. A material safety data sheet outlining proper handling of this product is available upon request, or will be forwarded upon the purchase of **Chem Flo - 203**.