

Gas Well Supply

5003 Summerbrook Dr, Colleyville, Texas U.S.A 76034

Ph: (530) 846-4400 1 (866) 202-STIX

Fax: (530) 846-4500

Product Bulletin

Chem Dual 101 Corrosion/Scale Inhibitor

PRINCIPAL USES

- Producing oil and gas wells
- Water supply wells
- Water injection wells, flowlines and surface vessels
- Controls carbonate and sulfate scales
- Controls H₂S or CO₂ corrosion
- Cleans dirty systems

PRODUCT BENEFITS

Chem Dual 101 is a balanced blend of water soluble corrosion and scale inhibitors designed to control calcium carbonate scaling and corrosion from H₂S or CO₂. Chem Dual 101 exhibits excellent detergent action, producing and maintaining a clean system.

GENERAL DESCRIPTION

Form....Liquid Color....Dark amber Odor....Petroleum smell Solubility....Water soluble Specific Gravity....1.035 Pour Point....>-30°F Density....8.64 lbs./gal pH....7 - 8

DOSAGES AND FEEDING

Continuous treatment is recommended when using Chem Dual 101. Concentrations will range from 40 to 100 ppm depending on the type of system being treated and the severity of the problem. For best results with batch treatment, the wells should have at least 200 feet or more fluid level above the pump, providing a reservoir of chemical between treatments.



Gas Well Supply

5003 Summerbrook Dr, Colleyville, Texas U.S.A 76034

Ph: (530) 846-4400 1 (866) 202-STIX

Fax: (530) 846-4500

SAFETY AND HANDLING

Causes irritation to skin and eyes. Do not get in eyes, on skin or on clothing. Wear goggles and rubber gloves when handling. Remove contaminated clothing and wash before use. In case of contact, immediately flush with large amounts of water; for eyes, also get medical attention. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation. Do not use, store, spill or pour near heat, sparks or open flame. Keep container closed when not in use.

For additional information see SDS.

For medical and transportation emergencies involving Gas Well Supply products, please call (530) 870-7667.

SHIPPING

Chem Dual 101 is shipped in nonreturnable lined steel 55 gallon drums and in bulk quantities to customer locations.

DISCLAIMER OF LIABILITY: Gas Well Supply believes the information presented in this bulletin to be accurate but all recommendations are made without warranty since the conditions of use are beyond Gas Well Supply's control. The data provided is illustrative only and not product specifications. Gas Well Supply expressly disclaims any and all warranties including those of merchantability and of fitness for a particular purpose or use of this product.