



Gas Well Supply

5003 Summerbrook Dr, Colleyville, Texas U.S.A 76034

Ph: (530) 846-4400 1 (866) 202-STIX

Fax: (530) 846-4500

Product Bulletin

Chem Flo 201 Corrosion Inhibitor

PRINCIPAL USES

Chem Flo 201 is specially formulated to be equally effective against CO₂ (carbon dioxide) and H₂S (hydrogen sulfide) corrosion. Chem Flo 201 has excellent surfactant and anti-foulant properties, which makes it the product of choice in dirty systems where under-deposit corrosion can be a problem. Chem Flo 201 is soluble in a wide variety of brines and it is oil dispersible, allowing for continuous or batch treatments in oil, gas, or injection wells.

PRODUCT BENEFITS

- Forms tenacious film on metal surfaces
- Films in oil-free systems
- Effective against H₂S or CO₂ corrosion
- Excellent for high fluid level wells
- Cleans dirty surfaces
- Controls under-deposit corrosion
- Can be batch treated

GENERAL DESCRIPTION

Form....Liquid	Specific Gravity....0.94
Color....Dark	Pour Point....<-10°F
Odor....Alcohol	Density....7.8 – 8.2 lbs./gal
Solubility....Water, Brines, Crude oil	pH....7.0 – 8.0

DOSAGES AND FEEDING

Chem Flo 201 can be applied continuously with a chemical feeder, or can be batch circulated, or truck treated. Dosage will vary with individual well conditions and severity of the corrosion. Dosages of 40-120 ppm, based upon total fluid produced, is usually adequate to provide the protection desired. Consult with Gas Well Supply for specific recommendations.



Gas Well Supply

5003 Summerbrook Dr, Colleyville, Texas U.S.A 76034

Ph: (530) 846-4400 1 (866) 202-STIX

Fax: (530) 846-4500

SAFETY AND HANDLING

Causes irritation to skin and eyes. Do not get in eyes, on skin or on clothing. Wear goggles and rubber gloves when handling. In case of contact, flush with large amounts of water; for eyes, also get medical attention. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation. Do not use, store, spill or pour near heat, spark or open flame. Keep container closed when not in use.

For additional information see SDS.

For medical and transportation emergencies involving Gas Well Supply products, please call (530) 870-7667.

SHIPPING

Chem Flo 201 is shipped in nonreturnable steel 55 gallon drums and in bulk quantities to customer locations.

DISCLAIMER OF LIABILITY: Gas Well Supply believes the information presented in this bulletin to be accurate but all recommendations are made without warranty since the conditions of use are beyond Gas Well Supply's control. The data provided is illustrative only and not product specifications. Gas Well Supply expressly disclaims any and all warranties including those of merchantability and of fitness for a particular purpose or use of this product.