

Gas Well Supply

5003 Summerbrook Dr, Colleyville, Texas U.S.A 76034 Ph: (530) 846-4400 1 (866) 202-STIX Fax: (530) 846-4500

Product Bulletin

Chem Treat 403 Pour Point Depressant

PRINCIPAL USES

- Great pour point depressant
- May be used as paraffin inhibitor in some instances
- Effective in keeping pressures in flowlines down
- Continuous treatment down the backside of the well
- Highly effective in combating paraffin build up when applied properly

GENERAL DESCRIPTION

Form....Liquid Color....Brown Odor....Aromatic Solubility....Oil soluble Specific Gravity....0.88 Pour Point....-20⁰F Density....7.33 lbs./gal pH....6.5 – 8.5

DOSAGES AND FEEDING

Chem Treat 403 can be used straight from the drum with a chemical pump. Normal treatment rates will range from 40 to 120 ppm depending on the type and severity of paraffin tendencies present. As well as the total volume of fluid being produced. Chem Treat 403 should fed continuously down the backside of the well to ensure the product is established in the oil phase.

SAFETY AND HANDLING

Causes irritation to skin and eyes. Do not get in eyes, on skin or on clothing. Wear goggles and rubber gloves when handling. In case of contact, immediately flush with large amounts of water; for eyes, also get medical attention. Avoid prolonged or repeated breathing of vapor. Use with adequate ventilation. Flammable! Do not use, store, spill or pour near heat, sparks or open flame. Keep container closed when not in use. For additional information see SDS.

For medical and transportation emergencies involving Gas Well Supply products, please call (530) 870-7667.



Gas Well Supply

5003 Summerbrook Dr, Colleyville, Texas U.S.A 76034 Ph: (530) 846-4400 1 (866) 202-STIX Fax: (530) 846-4500

SHIPPING

Chem Treat 403 is shipped in nonreturnable steel 55 gallon drums and in bulk quantities to customer locations.

DISCLAIMER OF LIABILITY: Gas Well Supply believes the information presented in this bulletin to be accurate but all recommendations are made without warranty since the conditions of use are beyond Gas Well Supply's control. The data provided is illustrative only and not product specifications. Gas Well Supply expressly disclaims any and all warranties including those of merchantability and of fitness for a particular purpose or use of this product.